



GKL-R-S-100 PTE/K 80 301811
















Product type: Swivel castors with directional lock
Product group: Tango

The Tango equipment castor is suitable for environments where features like stainless material, conductivity or non-magnetic. The smoothly rolling and maintenance-free Tango is manufactured of glassfibre-reinforced polyamide. With its perfect design, the Tango castor is easy to clean and suitable for most environments. Tango is the right choice, whether the environment is a hospital, rehabilitation centre, institutional kitchen, restaurant, shop, office, public facility or factory.



www.manner.fi/en/tuote/gkl-r-s-100-pte-k-80

Technical data

| | | | | | |
|---|-------------------------------|------------|---|-----------------------------------|-----------------------|
|  | Wheel diameter (mm): | 100 | Sh A | Hardness of the tread (shore A): | 80 |
|  | Wheel width (mm): | 32 |  | Centre material: | Polypropylene |
|  | Load capacity (kg): | 100 |  | Bearing type: | Ball bearing |
|  | Overall height (mm): | 148 |  | Fitting: | Rectangular top plate |
|  | Swivel radius (mm): | 95 |  | Weight (kg): | 0.52 |
|  | Plate length x width (mm): | 77X67 |  | Hole centres length x width (...) | 61/51X50/42 |
|  | Fastening hole diameter (mm): | 8 |  | Brake type: | Directional brake |
|  | Brake control: | Individual |  | Tread material: | Thermoplastic rubber |