



## GKL-R-S-125 NP/K 304047













**Product type:** Swivel castors with directional lock  
**Product group:** Tango

The Tango equipment castor is suitable for environments where features like stainless material, conductivity or non-magnetic. The smoothly rolling and maintenance-free Tango is manufactured of glassfibre-reinforced polyamide. With its perfect design, the Tango castor is easy to clean and suitable for most environments. Tango is the right choice, whether the environment is a hospital, rehabilitation centre, institutional kitchen, restaurant, shop, office, public facility or factory.



[www.manner.fi/en/tuote/gkl-r-s-125-np-k](http://www.manner.fi/en/tuote/gkl-r-s-125-np-k)

### Technical data

 Wheel diameter (mm):	125	<b>Sh A</b> Hardness of the tread (shore A):	80
 Wheel width (mm):	32	 Centre material:	Polyamide
 Load capacity (kg):	100	 Bearing type:	Ball bearing
 Overall height (mm):	168	 Fitting:	Rectangular top plate
 Swivel radius (mm):	110	 Weight (kg):	0.62
 Plate length x width (mm):	77X67	 Hole centres length x width (...)	61/51X50/42
 Fastening hole diameter (mm):	8	 Brake type:	Directional brake
 Brake control:	Individual	 Tread material:	Soft polyurethane