



## GKL-R-S-75 PTE/K 80 301803



















**Product type:** Swivel castors with directional lock  
**Product group:** Tango

The Tango equipment castor is suitable for environments where features like stainless material, conductivity or non-magnetic. The smoothly rolling and maintenance-free Tango is manufactured of glassfibre-reinforced polyamide. With its perfect design, the Tango castor is easy to clean and suitable for most environments. Tango is the right choice, whether the environment is a hospital, rehabilitation centre, institutional kitchen, restaurant, shop, office, public facility or factory.



[www.manner.fi/en/tuote/gkl-r-s-75-pte-k-80](http://www.manner.fi/en/tuote/gkl-r-s-75-pte-k-80)

### Technical data

 Wheel diameter (mm):	75	<b>Sh A</b> Hardness of the tread (shore A):	80
 Wheel width (mm):	32	 Centre material:	Polypropylene
 Load capacity (kg):	70	 Bearing type:	Ball bearing
 Overall height (mm):	117	 Fitting:	Rectangular top plate
 Swivel radius (mm):	94	 Weight (kg):	0.48
 Fork material:	Plastic	 Plate length x width (mm):	77X67
 Hole centres length x width (...)	61/51X50/42	 Fastening hole diameter (mm):	8
 Brake type:	Directional brake	 Brake control:	Individual
 Color:	Grey	 Bore length (mm):	
 Tread material:	Thermoplastic rubber		