



## GK-S-125 PTE/K A 301833

<b>Product type:</b>	Swivel castors
<b>Product group:</b>	Tango Conductive

The Tango equipment castor is suitable for environments where features like stainless material, conductivity or non-magnetic. The smoothly rolling and maintenance-free Tango is manufactured of glassfibre-reinforced polyamide. With its perfect design, the Tango castor is easy to clean and suitable for most environments. Tango is the right choice, whether the environment is a hospital, rehabilitation centre, institutional kitchen, restaurant, shop, office, public facility or factory.



[www.manner.fi/en/tuote/gk-s-125-pte-k-a](http://www.manner.fi/en/tuote/gk-s-125-pte-k-a)

### Technical data

 Wheel diameter (mm):	125	<b>Sh A</b> Hardness of the tread (shore A):	86
 Wheel width (mm):	32	 Centre material:	Conductive polypropylene
 Load capacity (kg):	80	 Bearing type:	Ball bearing
 Overall height (mm):	161	 Fitting:	Bolt hole
 Swivel radius (mm):	110	 Bolt hole diameter (mm):	10
 Weight (kg):	0.434	 Fork material:	Conductive glass fiber reinforced polyamide
 Color:	Dark grey	 Bore length (mm):	
 Special features:	Conductive	 Tread material:	Conductive thermopl. rubber