



## GKL-JY-S-100 PTE/K A 301851




















<b>Product type:</b>	Swivel castors with brake
<b>Product group:</b>	Tango
	Conductive

The Tango equipment castor is suitable for environments where features like stainless material, conductivity or non-magnetic. The smoothly rolling and maintenance-free Tango is manufactured of glassfibre-reinforced polyamide. With its perfect design, the Tango castor is easy to clean and suitable for most environments. Tango is the right choice, whether the environment is a hospital, rehabilitation centre, institutional kitchen, restaurant, shop, office, public facility or factory.



[www.manner.fi/en/tuote/gkl-jy-s-100-pte-k-a](http://www.manner.fi/en/tuote/gkl-jy-s-100-pte-k-a)

### Technical data

 Wheel diameter (mm):	100	<b>Sh A</b> Hardness of the tread (shore A):	86
 Wheel width (mm):	32	 Centre material:	Conductive polypropylene
 Load capacity (kg):	80	 Bearing type:	Ball bearing
 Overall height (mm):	148	 Fitting:	Rectangular top plate
 Swivel radius (mm):	95	 Weight (kg):	0.529
 Fork material:	Plastic	 Plate length x width (mm):	77X67
 Hole centres length x width (...)	61/51X50/42	 Fastening hole diameter (mm):	8
 Brake type:	Total-stop brake	 Brake control:	Individual
 Color:	Dark grey	 Bore length (mm):	
 Special features:	Conductive	 Tread material:	Conductive thermopl. rubber