



GKL-JY-S-125 PTE/K A 301853




















Product type:	Swivel castors with brake
Product group:	Tango Conductive

The Tango equipment castor is suitable for environments where features like stainless material, conductivity or non-magnetic. The smoothly rolling and maintenance-free Tango is manufactured of glassfibre-reinforced polyamide. With its perfect design, the Tango castor is easy to clean and suitable for most environments. Tango is the right choice, whether the environment is a hospital, rehabilitation centre, institutional kitchen, restaurant, shop, office, public facility or factory.



www.manner.fi/en/tuote/gkl-jy-s-125-pte-k-a

Technical data

 Wheel diameter (mm):	125	Sh A Hardness of the tread (shore A):	86
 Wheel width (mm):	32	 Centre material:	Conductive polypropylene
 Load capacity (kg):	80	 Bearing type:	Ball bearing
 Overall height (mm):	168	 Fitting:	Rectangular top plate
 Swivel radius (mm):	110	 Weight (kg):	0.605
 Fork material:	Conductive glass fiber reinforced polyamide	 Plate length x width (mm):	77x67
 Fastening hole diameter (mm):	8	 Hole centres length x width (...)	61/51X50/42
 Brake control:	Individual	 Brake type:	Total-stop brake
 Bore length (mm):		 Color:	Dark grey
 Tread material:	Conductive thermopl. rubber	 Special features:	Conductive