



GKR-JY-S-125 PTE/K A 301842


















Product type:	Swivel castors with brake
Product group:	Tango Conductive

The Tango equipment castor is suitable for environments where features like stainless material, conductivity or non-magnetic. The smoothly rolling and maintenance-free Tango is manufactured of glassfibre-reinforced polyamide. With its perfect design, the Tango castor is easy to clean and suitable for most environments. Tango is the right choice, whether the environment is a hospital, rehabilitation centre, institutional kitchen, restaurant, shop, office, public facility or factory.



www.manner.fi/en/tuote/gkr-jy-s-125-pte-k-a

Technical data

 Wheel diameter (mm):	125	Sh A Hardness of the tread (shore A):	86
 Wheel width (mm):	32	 Centre material:	Conductive polypropylene
 Load capacity (kg):	80	 Bearing type:	Ball bearing
 Overall height (mm):	161	 Fitting:	Threaded stem
 Swivel radius (mm):	110	 Weight (kg):	0.507
 Fork material:	Conductive glass fiber reinforced polyamide	 Threaded stem diameter x len...	10X16
 Brake control:	Individual	 Brake type:	Total-stop brake
 Bore length (mm):		 Color:	Dark grey
 Tread material:	Conductive thermopl. rubber	 Special features:	Conductive